

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 331)

-----  
Set a sandstone, 10x10x6", 7" in the ground, for ¼ sec. cor., marked ¼ S on W face; and raised a mound of stone, 1½ ft. high and 2 ft. base, alongside. Pits Impracticable.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12523)

-----  
Point for the ¼ sec. cor. of secs. 19 & 20, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground with brass cap marked:

¼  
S 19|S 20  
1953

from which

- A fir, 50" dia., bears S.37°45'E., 48 lks., mkd: ¼ S20 BT.
- A cedar, 20" dia., bears S.28¼°W., 29 lks., mkd: ¼ S19 BT.