

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T19-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 44 Page(s) 17053)

Set a Fir post 3 ft.long, 4" sq., 24" in the ground for cor. of secs. 32 and 33, marked T19S S33 on NE. face, and R9W S32 on NW. face, with 4 notches on E. and 2 notches on W. edges, from which

A Fir 6" dia., bears N.15°E., 20 lks. dist. mkd. T19S R9W S33 BT.

A Fir 8" dia., bears N.20°W., 10 lks. dist. mkd. T19S R9W S32 BT.

The old cor. bears East, 4 lks. dist. I destroy it.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 375)

(Apportioned distance) Set an iron post 3 ft.long, 2" dia., 27" in the ground for re-established cor. of secs. 32 and 33, T19S R9W, with brass cap mkd:

T19S R9W
S32 S33
S 5
T20S R9W
1921

from which

An Alder 30" dia., bears N.55°E., 57 lks. dist. mkd. T19S R9W S33 BT.

A Fir 20" dia., bears N.83°W., 34 lks. dist. mkd. T19S R9W S32 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - July 19, 1968 - C.S. File 53/66

Found - 1921 GLO brass cap in place and firmly set.
Orig. 20" now 26" Fir sawed stump, N.83°W., 22.4 ft., shows scar.

No trace other BT, due to slide.

There being no trees close, we set

5/8" I.Rod in front of BT stump on N.83°W., bearing 20.9 ft.

5/8" I.Rod North 10.0 ft.

6 ft. steel fence post alongside brass cap.

This corner lies on very steep northerly slope approx. 200 ft. from log landing in sec. 5.

(Cont. Next Page)

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 271700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15451)

The Sec. cor., monumented with an iron post 2" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1921, from which the remains of the original bearing trees

A sawed Fir stump 24" dia., bears N.83°W., 34 lks. dist., with healed blaze.

No suitable trees available within limits.

Drive a 6 ft. steel fence post alongside iron post.