

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T21-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Wm. Thiel under Contract #260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 304)

Near head of canyon. Set a rock 30x16x16, with 3 smaller ones piled around, for cor. to secs. 32, 33, 4 and 5; from which

- A Fir 40" dia., bears S.33¼°E., 1.16 chs. dist.
- A Fir 36" dia., bears S.33½°W., 1.86 chs. dist.
- A Cedar 30" dia., bears N.49 3/4°W., 1.22 chs. dist.
- A Fir 36" dia., bears N.29¼°E., 33 lks. dist.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 1 Page(s) 366)

The cor. to secs. 32 and 33, which is a rock in place, 30x20x16 ins. above ground, marked with 2 notches on the West and 4 notches on the East sides, with a X on top of stone; from which

- A dead Fir 36" dia., bears N.29°E., 33 lks. dist. mkd. T20S R9W S33 BT.
- A Fir 40" dia., bears S.33°15'E., 116 lks. dist. mkd. T21S R9W S4 BT.
- A Fir 36" dia., bears S.33°30'W., 188 lks. dist. mkd. T21S R9W S5 BT.
- A Cedar 36" dia., bears N.49°45'W., 122 lks. dist. mkd. T20S R9W S32 BT.

Oct. 8, 1894

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12448-49)

The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone 30" x 20" x 18", with no marks remaining, from which the original bearing trees:

- A Fir stump 36" dia., bears N.29¼°E., 33 lks. dist., with partial scribe marks visible. (Gesner record, bears N.29°E.)
- A Fir 60" dia., bears S.33¼°E., 115 lks. dist., plainly blazed and healed. (Rec. 116 lks. dist.)
- A Fir 72" dia., bears S.33½°W., 182 lks. dist. plainly blazed and healed. (Thiel record, 186 lks. dist.; Gesner record, 188 lks. dist.)
- A Cedar stump 56" dia., bears N.49°45'W., 124 lks. dist., plainly blazed and healed. (Rec. 122 lks. dist.)

At the corner point

(Cont. Next Page)

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, and in a small mound of stone, to top, with brass cap mkd:

T 20 S R 9 W

S 32 S 33

S 5 S 4

T 21 S

1953

from which new bearing trees:

A Fir 12" dia., bears N.41°45'E., 95 lks. dist., mkd. T20S R9W S33 BT.

A Hemlock 36" dia., bears N.29°W., 122 lks. dist. mkd. T20S R9W S32 BT.

Reset the sandstone alongside the iron post.

From this point, a Maple 12" dia., bears S.39°W., 33 lks. dist., with partially healed blazes on N., S., E., and W. sides.

Fd. OK and used in BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14217)

Fd. OK, Dec. 1982 by Les Roberts - M 90-30