TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 335)

Set a sandstone, 9x9x7, 6" in the ground, for ¼ sec. cor. marked ¼ on W face; & raised a mound of stone, 1½ ft. high & 2 ft. base, alongside. Pits impracticable.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12511-2

Point for the ¼ sec. cor. of secs. 20 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 20|S 21
1953

from which

A fir, 8" dia., bears S.18°E., 31 lks., mkd: ¼ S21 BT.
A fir, 18" dia., bears N.85°W., 32 lks., mkd: ¼ S20 BT.

The ¼ sec. cor. falls at a junction of spurs, from E., slope NW & SW.

Fd. Ok by Les Roberts Dec. 1982 - M90-31