

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 338)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
An Alder, 10" dia., bears N.86½°E., 63 lks., mkd: ¼ S BT.
A maple, 30" dia., bears S.70°W., 50 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12510-1)

The ¼ sec. cor. of secs. 21 & 28, at rec. bearing & dist. from each of the orig. BTs, as follows:

An Alder, 28" dia., bears N.86½°E., 63 lks., with partial scribe marks visible on decayed face of partly healed blaze.

A double maple, 70" dia., bears S.70°W., 50 lks., with blaze healed.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼ $\frac{S\ 21}{S\ 28}$
1953

from which a new BT

A fir, 66" dia., bears N.17°45'SW., 47 lks., mkd: ¼ 21 BT.

Fd. Ok by Les Roberts Dec. 1982 - M90-31

FD. Ok by Les Roberts 10/10/1984 - C.S. File 58/237