TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 340-1)

---

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
A fir, 24" dia., bears S.5°W., 16 lks., mkd: ¼ S BT.
A fir, 32" dia., bears N.48½°E., 9 lks., mkd: ¼ S BT.

---

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12513

---

Point for the ¼ sec. cor. of secs. 16 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground with brass cap marked:

¼ S 16 / S 21
1953

from which
A cascara, 6" dia., bears N.30°E., 33 lks., mkd: ¼ S16 BT.
A cascara, 8" dia., bears S.63°W., 41 lks., mkd: ¼ S21 BT.

---

Les Roberts - For: International Paper - 12/10/1982 - M90-31

---

Found - 1953 GLO BC
No 1953 BTs fd.
New BTs- 44" fir bears N.87°W., 22.5 ft. (scribed)
80" fir bears S.10°E., 88.0 ft. (scribed)

---