

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 324)

-----  
Set a post, 3 ft. long, 3" sq., 12" in the ground, for 1/4 sec. cor., marked 1/4 S on W face; from which  
A fir, 24" dia., bears N.24 1/2°W., 88 lks., mkd: 1/4 S BT.  
A fir, 18" dia., bears S.34°E., 28 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12481)

-----  
Point for the 1/4 sec. cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

1/4  
S 34 | S 35  
1953

from which  
A fir, 7" dia., bears S.16 1/2°E., 24 1/2 lks., mkd: 1/4 S35 BT.  
A fir, 8" dia., bears N.41°W., 3 lks., mkd: 1/4 S34 BT.

Fd. Ok by Les Roberts, 2/19/1984 - M96-26 & C.S. File 58/280