

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 347)

Set a post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
A fir, 20" dia., bears S.75½°W., 18 lks., mkd: ¼ S BT.
A fir, 45" dia., bears N.47°E., 29 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12488-9)

The ¼ sec. cor. of secs. 14 & 15, determined at rec. bearing & dist. from each of the orig. BTs, as follows:

A fir, 60" dia., bears N.47°E., 29 lks., with no marks remaining on scaled bark blaze.
A fir, 35" dia., bears S.75½°W., 18 lks., mkd. ¼ S BT on bark blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, and in a mound of stone, 2 ft. base, to top with brass cap marked:

¼
S 15|S 14
1953

from which new BTs

A fir, 60" dia., bears N.85½°E., 56 lks., mkd: ¼ S14 BT.
A fir, 35" dia., bears S.67½°W., 57 lks., mkd: ¼ S15 BT.

Fd. Ok by Les Roberts 2/28/1983 - M93-64