

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500636

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 350)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which

 An alder, 6" dia., bears S.52°E., 37 lks., mkd: ¼ S BT.

 A fir, 40" dia., bears N.25°W., 28 lks., mkd: ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 384)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap marked:

¼
S 3
1921

from which

 A fir, 40" dia., bears S.86°W., 36 lks., mkd: ¼ S3 BT.

 A fir, 36" dia., bears N.37°W., 88 lks., mkd: ¼ S3 BT.

Fd. Ok by D. Peel, 6/1982 - M 92-28