

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 325)

Set a sandstone, 10x8x8", 7" in the ground, for 1/4 sec. cor. marked 1/4 on W face; and raised a mound of stone, 1 1/2 ft. high, 2 ft. base, alongside. Pits impracticable.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12462)

Point for the 1/4 sec. cor. of secs. 35 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4
S 35 | S 26
1954

from which

- A hemlock, 31" dia., bears N.70°E., 111 lks. mkd: 1/4 S36 BT
- A hemlock, 12" dia., bears N.75°W., 58 lks., mkd: 1/4 S35 BT

Les Roberts, PLS 1039 - For: Internation Paper - March 1984 - M 96-26 & C.S. File 58/280

Found - No evidence fd. of brass cap or BTs set by GLO in 1954. Corner falls in steep & narrow creek bottom. Creek has been torn up by old logging.

Set - 2"x36" alum. pipe & cap by proportionate measure. Buried purple magnetic marker under cap. Cap stamped T20S R9W 1/4 Cor S35+S36 1984 PLS 1039

Set - 2"x36" alum. pipe & cap for witness corner. WC bears N.2°01'02"E., 30.0 ft. from 1/4 cor. Buried purple magnetic marker under 36" alum. pipe. Cap stamped "T20S R9W WC S35 + S36 1984 PLS 1039"

New - 8" alder, N.54°E., 20.0 ft. Bark scribed/painted /brass washer.

Metal fence post beside brass cap. Wired survey monument sign to fence post.

Corner lies 8 ft. south of 2 ft. creek in steep narrow canyon.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22898)

The 1/4 sec. cor. of secs. 35 & 36, reestablished by proportionate measurement by Roberts, in 1984. There is no remaining evidence of the original cor. or (cont.)

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

. . . the cor. reestablished by proportionate measurement by Tillman and Gawron, therefore this point is accepted as the cor.; determined at record bearing and dist. from the bearing tree by Roberts

An alder, 17" dia., bears N.54°E., 20.0 ft., with illegible scribe marks visible on bark.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with bronze cap mkd. T20S R9W

¼
S 35|S 36
2011

from which a witness cor. established by Roberts

An aluminum post, 2" dia., firmly set, projecting 8" above ground, bears N.2°03'50"E, 30.00 ft., with bronze cap mkd. INTERNATIONAL PAPER CO UNLAWFUL TO DISTURB T20S R9W W.C. S35 + S36 1984 PLS 1039 CADASTRAL SURVEY IP TIMBERLANDS. A steel fence post is alongside the witness cor. This monument now functions as a reference monument.

A fir, 16" dia., bears N.86½°W., 19.2 ft., mkd. ¼ S35 BT. Deposit a magnet in a white plastic case at the base of the stainless steel post. Drive found steel fence post alongside the cor., which falls in a creek, dry, 2 ft. wide, course N.50°W., near the W. side of the bottom of a steep-sided gully.