

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 357)

-----  
Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which  
A fir, 50" dia., bears N.47°E., 27 lks., mkd: ¼ S BT.  
A fir, 30" dia., bears S.40°W., 56 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12472)

-----  
The ¼ sec. cor. of secs. 13 & 14 determined from the orig. BTs, as follows:  
A fir snag, 60" dia., bears N.47°E., 27 lks., with illegible scribe marks on bark blaze.  
A fir, 47" dia., bears S.40°W., 56 lks., with no marks remaining on badly scaled bark blaze.  
At the corner point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼  
S 14 | S 13  
1953  
from which new BTs  
A hemlock, 12" dia., bears S.31½°E., 20 lks. mkd: ¼ S13 BT  
An alder, 14" dia., bears S.73°W., 40 lks., mkd: ¼ S14 BT.

FD. Ok by Les Roberts - 2/28/1983 - M93-64

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22905)

-----  
The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 1" dia., firmly set, projecting 2" above ground, with a bronze cap (properly) mkd.  
from which the remains of the original bearing trees  
A fir stump, size indeterminate, bears N.47°E., 21.1 ft., no marks visible. (Record, N.40°E.)  
A fir stump, 52" dia., bears S.48¾°W., 39.5 ft., no marks visible. (Record, S.44°W.)  
and a bearing tree mkd. by Tillman and Gawron in 1953-54  
An alder, 13" dia., bears S.76¾°W., 26.4 ft., no marks visible. (Record, S.73°W., 27.0 ft.) Tree is 20" dia. for 2 ft. high before narrowing abruptly; it appears to have been broken and regrown.  
and a bearing tree mkd. by Forkner in 2006-09  
continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias	Description

A fir, 24" dia., bears S.4°E., 12.6 ft., with a healed blaze. (Record, S.11°E., 13.6 ft.)  
An iron axle, 1" dia., firmly set, projecting 15" above ground, is alongside the cor  
Latitude: 43°50'04.79"N Longitude: 123°43'41.20"W  
NAD 1983 (CORS 96)

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23089-90)

-----  
The ¼ sec cor. of secs 13 & 14, monumented with an iron post, 1" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A fir stump, size indeterminate, bears N.40°E., 21.1 ft., no marks visible. (Record, N.47°E., 17.8 ft.)  
A fir stump, 52" dia., bears S.44°W., 39.5 ft., no marks visible. (Record, S.40°W., 37.0 ft.)  
and a bearing tree mkd. by Tillman and Gawron in 1953-54  
An alder, 12" dia. , bears S.73°W. , 27.0 ft., no marks visible. (Record, 26.4 ft.) This alder is 18" dia. for 2 ft. high before narrowing abruptly; it appears to have been broken and regrown.  
and a new bearing tree  
A fir, 21" dia., bears S.11°E., 13.6 ft., mkd. ¼ S13 BT.  
An iron axle, 1" dia., firmly set, projecting 16" above ground, established by person(s) unknown is alongside the cor.