

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 360-1)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 1, 2, 11, & 12, marked T20S S1 on NE, R9W S12 on SE, S11 on SW, S2 on NW faces, with 1 notch on E & 5 notches on S edges; from which

A fir, 24" dia. bears N.88°E., 15 lks. mkd: T20S R9W S1 BT  
A vine maple, 4" dia., bears S.32°E., 18 lks., mkd: T20S R9W S12 BT.  
A fir, 15" dia. bears S.47°W. 34 lks. mkd: T20S R9W S11 BT  
A fir, 24" dia., bears N.29°W., 4 lks. mkd: T20S R9W S2 BT

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12476-7)

-----

The cor. of secs. 1, 2, 11, & 12, determined at record bearing & dist. from each of the orig. BTs, as follows:

A fir, 40" dia., bears N.88°E., 15 lks., marked T20S R9W S1 BT on bark blaze.  
A vine maple, 8" dia., bears S.32°E., 18 lks. with scribe marks visible on partly healed blaze.  
A fir, 30" dia. bears S.47°W. 34 lks., marked T20S R9W S11 BT on bark blaze.  
A fir, 30" dia., bears N.29°W., 4 lks., marked T20S R9W S2 BT on bark blaze.

At the corner point  
Set an iron post, 3 ft long, 2" dia., 27" in the ground, with brass cap marked:

T20S	R9W
S 2	S 1
S 11	S 12
1953	

from which new BTs

A fir, 40" dia. bears N.71½°E., 59 lks mkd: T20S R9W S1 BT  
A hemlock, 10" dia., bears S.58½°E., 43 lks., mkd: T20S R9W S12 BT.  
A fir, 36" dia. bears S.5½°W., 56 lks mkd: T20S R9W S11 BT

Ronald L Rice - For: Oxbow Timber 1 LLC - Mar 2015 - M169-27

-----

Found - 1953 GLO brass cap with the following accessories:  
44" D.Fir bears N.88°E. 9.9' - bark scribe visible  
38" D.Fir bears S.47°W., 22.4' - bark scribe visible  
32" Hemlock bears S.58½°E., 28.4' - healed face  
33" D.Fir bears N.29°W., 2.6' - bark scribe visible  
Other accessories of record not searched for.

CONT

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2810, surveyed Sept. 2015/Jan. 2016 - (DCSO records Vol. 58 Page(s) 2347)

-----

The cor. of secs. 1, 2, 11, & 12, monumented with an iron post, 2" dia., firmly set, projecting 11" above ground, with a brass cap (properly) mkd.

from which the original bearing trees

A fir, 47" dia., bears N.88°E., 9.9 ft., with axe marks X at breast height, scribe marks 9W visible on bark, and other axe marks.

A fir, 41" dia., bears S.47°W., 22.4 ft., with scribe marks 12 S BT and other illegible scribe marks visible on bark.

A fir, 33" dia., bears N.29°W., 2.6 ft., with various cruiser marks.

and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A roothole bears N.71½°E., 38.9 ft., alongside of which is a uprooted fir stump, 35" dia., with no marks visible on decayed partially healed blaze.

A hemlock, 34" dia., bears S.58½°E., 28.4 ft., with a healed blaze.

A roothole bears S.5½°W., 37.0 ft., alongside of which is a down decayed fir, 36" dia., no marks visible.

An aluminum fence post with a Forest Service sign is alongside the cor.