

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 327)

-----

A maple 8" dia., which I marked 1/4 S on N side, for 1/4 sec. cor.; from which

A fir, 36" dia., bears N.50°W., 31 lks., mkd: 1/4 S BT.

A fir, 30" dia., bears S.77°W., 24 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12463)

-----

The 1/4 sec. cor. of secs. 25 & 36, in earth-filled hollow bet. forks of the orig. corner tree, a maple, 28" dia., with healed blaze on N side, from which the orig. BTs

A fir, 43" dia., bears N.5°W., 38 lks., mkd: 1/4 S BT on bark blaze. (Rec. bears N.50°W., 31 lks.)

A fir, 48" dia., bears West, 21 lks., mkd: 1/4 S BT on bark blaze. (Rec. bears S.77°W., 24 lks.)

The BTs do not match the rec., but are marked in the manner used by Thiel at other corners, & face the corner point.

The maple corner tree leans sharply to the E above a bluff, 6 ft. high facing E.; the west side of the tree has decayed & left a pocket of earth at the center of the base of the tree, therefore,

At the corner point

Set an iron post, 3 ft. long, 1" dia., 12" in the ground, to solid rock, & in a mound of stone, to top, with brass cap marked:

$$\frac{1}{4} \begin{array}{l} \text{S } 25 \\ \text{S } 36 \end{array}$$

1954

from which

A hemlock, 10" dia., bears N.43 1/4°W., 38 lks. mkd: 1/4 S25 BT

A cedar, 13" dia., bears S.17 1/2°W., 47 lks., mkd: 1/4 S36 BT.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22900)

-----

The 1/4 sec. cor. of secs. 25 & 36, monumented with the remains of the original cor. tree, a collar of maple sprouts, the largest of which is 8" dia., from which the remains of the original bearing trees

A decayed fir stump, 33" dia., bears West, 13.9 ft., no marks visible.

A decayed fir stump, 41" dia., bears N.5°W., 25.1 ft., no marks visible. (Record, N.5°E.)

continued next pg

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a BT mkd. by Tillman and Gawron in 1953-54  
A decayed cedar stump, 16" dia., bears S.15°W., 30.0 ft.,  
with illegible scribe marks visible on open decayed  
blaze. (Record and slope, S.17½°W., 31.0 ft.)  
and new bearing trees and a witness corner  
A fir, 14" dia., bears N.16½°E., 11.7 ft., mkd. ¼ S25 BT.  
The 1953-54 iron post, 36" long, 1" dia., found lying  
loose, reset 29" in the ground for a witness corner,  
bears S.35°00'00"W, 15.00 ft., with bronze cap now mkd.  
WC T20S R9W S25 ¼ S36 2011 1954. Deposit a magnet in  
a white plastic case at the base of the iron post.  
A fir, 11" dia., bears S.70¼°W., 29.8 ft., mkd. ¼ S36 BT.  
The true cor. falls on the south side of the collar of maple  
sprouts, on a large root, on the top of a rock bluff, 6 ft.  
high, faces E., on a steep E. slope, and is impractical to  
remonument.