

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 362)

A vine maple, 5" dia., which I marked ¼S on N face, for ¼ sec. cor.; from which

A fir, 24" dia., bears N.34°W., 10 lks., mkd: ¼ S BT.

A fir, 27" dia., bears S.88°E., 11 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12478)

The ¼ sec. cor. 1 & 12, determined at rec. bearing & dist. from which each of the orig. BTs, as follows:

A fir, 30" dia., bears N.34°W., 10 lks., with only the marks BT remaining on badly scaled bark blaze.

An uprooted fir, 30" dia., with no marks remaining, the stump hole of which bears S.88°E., 11 lks.

At the corner point

Set an iron post, 3 long, 1" dia., 27" in the ground, with brass cap marked:

¼ $\frac{S \ 1}{S \ 12}$
1953

from which a new BT,

A fir, 32" dia., bears S.14½°W., 35 lks., mkd: ¼ S12 BT.

Donald Branch - For: International Paper Co. - 2/3/1987 - M101-14 - & C.S. File 63/48

Found - 1" BLM cap marked "T20S R9W ¼ S1 S12 1954

22" Fir snag bears N.37°W., 6.7 ft.

21" Fir snag bears S.16°W., 23.5 ft. with bark scribing & tag.

New BTs- 8" D.Fir bears N.5°E., 14.0 ft. scribed "¼ S1 BT"

8" D.Fir bears S.8°E., 3.1 ft. scribed "¼ S12 BT"

Note: Set a 6' alum post with attention sign next to monument

FD. Ok by Wayne Donovan, 5/19/1993 - C.S. File 63/153

Ronald L Rice - For: Oxbow Timber 1 LLC - Mar 2015 - M169-27

Found - 1953 GLO brass cap with the following accessories:

12" D.Fir staub bears N.37°W., 6.7' - no marks

18" D.Fir snag bears S.16°W., 23.5' - no marks

13" D.Fir bears N.5°E., 14.0' - healed face

13" D.Fir bears S.8°E., 3.1' - healed face

New BT - 15" D.Fir bears N.74°E. 8.7'-blazed, scribed ¼ S1 BT
Post adjacent to corner