

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 205)

-----  
Set a post 4 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which

A Fir 30" dia., bears S.13½°E., 10 lks. dist., mkd. ¼ S BT  
A Fir 24" dia., bears N.29°W., 29 lks. dist., mkd. ¼ S BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12460)

-----  
The ¼ sec. cor. of sec. 1, determined from the original bearing trees, as follows:

A Fir 30" dia., bears S.13½°E., 10 lks. dist. mkd. ¼ S BT on bark blaze.

A Fir 24" dia., bears N.29°W., 29 lks. dist. with faint scribe marks visible on badly scaled bark blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼ S 1  
1953

from which new bearing trees,

A Fir 24" dia., bears S.55¼°E., 59 lks., mkd. ¼ S1 BT.

A Fir 16" dia., bears S.69°W., 42 lks. mkd. ¼ S1 BT

Wayne R. Donovan, LS #2553 - Mike Kessler - 5/19/93 - C.S. File 63/153

-----  
Found - 1953 G.L.O. Brass cap in good condition.  
2½" brass cap bears N.89°12'50"W., 81.75' - (¼ cor. sec. 36.)

22" Fir, stump bears S.55½°E., 37.8', visible scribing.

20" Fir, stump bears S.69°W., 27.4', healed face.

New BTs- 17" Fir, bears S.22½°W., 53.8', blazed & scribed "¼ S1 BT"

10" Fir, bears S.43 ¾°E., 15.6', blazed & scribed "¼ S1 BT"

Corner lies on a gradual NW slope.

Ron Rice, NW Land Surveying - Jason Collver - May 2012 - C.S. File 65/76-51

-----  
Condition report only

Found - 2½" GLO brass cap on iron pipe, dated 1953  
continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

22" Fir, stump bears S.55½°E., 37.8', visible scribing. (Found in same condition)  
20" Fir, stump bears S.69°W., 27.4', healed face. (Found in same condition)  
17" Fir, bears S.22½°W., 53.8', blazed & scribed "¼ S1 BT" (Found 21" Fir with healed face)  
10" Fir, bears S.43¾°E., 15.6', blazed & scribed "¼ S1 BT" (Found 16" Fir with healed face)  
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.  
Compass Declination 16° East

Fd. BC & accessories per rec. by R.Rice - Mar 2015 - M169-27