

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 652100

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for Sec. 1 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14224)

Point for the ¼ sec. cor. of sec. 1 only, T21S R9W
Set an Iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

 ¼ S 1
 T 21 S R 9 W
 1967

from which

- A Fir 21" dia., bears S.51°E., 36½ lks. dist. mkd. ¼ S1 BT
- A Fir 28" dia., bears S.62°W., 72 lks. dist. mkd. ¼ S1 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2286, surveyed Oct. 2009 - (DCSO records Vol. 56 Page(s) 22335)

The ¼ sec. cor. of sec. 1 only, on the S. bdy. of T20S R9W established by Peterson in 1966-67; monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Peterson

- A fir snag, partially uprooted, leaning N, 28" dia., bears S.49½°E., 25.4 ft., no marks visible. (Record, S.51°E., 24.1 ft.)

- A fir, 37" dia., bears S.62°W., 47.5 ft., with a healed blaze.

and a new bearing tree

- A W.Fir, 10" dia., bears S.32¾°E., 45.7 ft., mkd. ¼ S1 BT.
- Corner is located on N. edge young second growth, edge bears N.85°E. and S.85°W.