

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T20-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 316)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor., marked 1/4 S on W face; from which
Alder 18" dia., bears N.40°W., 12 lks. dist. mkd. 1/4 S BT.
Alder 20" dia., bears S.49°E., 17 lks. dist. mkd. 1/4 S BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12348)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: *1/4 S 19
1954
from which
A Fir 25" dia., bears N.88 1/2°E., 107 lks. dist., mkd. 1/4 S19 BT.
A Hemlock 25" dia., bears S.56°E., 25 lks. dist. mkd. 1/4 S19 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16712)

The 1/4 sec. cor, monumented with an iron post 1" dia., firmly set, projecting 6" above ground with brass cap mkd. in 1954, from which bearing trees mkd. in 1954:
A Fir 42" dia., bears N.88 1/2°E., 107 lks. dist., with healed blaze.
A Hemlock 36" dia., bears S.56°E., 25 lks. dist., with scribe marks 1/4 visible on partially healed blaze.
Set a 5 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21751-2)

The 1/4 sec. cor. of sec. 19 only, monumented with an iron post, 1" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Tillman, et al., in 1953-54 continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700301

PRIMARY CORNER DESCRIPTION W. ¼ Cor. for Sec. 19 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 40" dia., bears N.88½°E., 70.6 ft., with no marks visible on partially healed blaze.
A hemlock stump, 33" dia., bears S.56°E., 16.5 ft., with a healed blaze.
and new bearing trees
A fir, 12" dia., bears N.19¼°E., 54.2 ft., mkd. ¼ S19 BT.
A fir, 19" dia., bears S.74¼°E., 83.7 ft., mkd. X BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22967)

The ¼ sec. cor. of secs. 19 only, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd. and accessories as described in the 2005 official survey by Graham.