

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Pages 206-07)

Set a Vine Maple post 4½ ft. long, 4" sq., 24" in the ground for closing cor. to Tps. 19 and 20 S., R 9 W., marked CC T19S S36 on N.; R8W on E.; T20S S1 on S.; CC R9W on W. faces, with 6 notches on N., S., & W. faces; from which

- A Fir 16" dia., bears S.55½°E., 30 lks. dist. mkd. CC T19 & 20 S R 9 W BT.
- A Fir 42" dia., bears S.70°W., 11 lks. mkd. T20S R9W S1 BT
- A Fir 40" dia., bears N.35½°W., 30 lks mkd T19S R9W S36 BT

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12461)

The closing cor., determined at the record bearing and distance from each of the original bearing trees, as follows:

- An uprooted Fir 22" dia., plainly blazed and healed, the stump hole of which bears S.55½°E., 30 lks.
- A Fir 52" dia., bears S.70°W., 11 lks. mkd. T20S R9W S1 BT on bark blaze.
- An uprooted Fir 60" dia., marked T19S R9W S36 BT on bark blaze, the stump hole of which bears N.35°W., 30 lks.

At the corner point

Set an iron post, 3 ft. long, 3" dia., 28" in the ground, with brass cap mkd:

T 19 S	
R 9 W	T 19 S
CC — S 36	S 31
S 1	
T 20 S	R 8 W
	1953

from which new bearing trees:

- A Fir 50" dia., bears N.7°W., 86 lks., mkd. T19S R9W S36 CC BT.
- A Fir 40" dia. bears S.38°W., 42 lks mkd T20S R9W S1 CC BT (From this point, the ¼ sec. cor. of S. 31, T19S R8W bears N.0°04'W., 2.02 chs. dist.)

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23081-2)

The closing cor. of Tps. 19 and 20 S. , R. 9 W. , monumented with an iron post, 3" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.

continued next page

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

from which the remains of an original bearing tree
A fir stump, 42" dia., bears S.70°W., 7.3 ft., no marks visible.
and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54
A decayed fir stump, 36" dia., bears S.38°W., 27.7 ft., no marks visible.
A fir stump, 56" dia., bears N.7°W., 56.8 ft., with axe marks on a burned partially healed blaze.
and new bearing trees
A fir, 11" dia., bears S.68°W., 34.2 ft. mkd. T20S R9W S1 CC BT.
A fir, 10" dia., bears N.65°W., 22.5 ft. mkd. T19S R9W S36 CC BT.

BLM dependent resurvey by Edith M Forkner & Jason A Lightbrown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23530-1)

The closing cor. of Tps. 19 & 20 S., R. 9 W., monumented with an iron post, 3" dia., firmly set, projecting 16" above ground, with a brass cap (properly) mkd.
from which the remains of an original bearing tree
A fir stump, 44" dia., bears S.70°W., 7.3 ft., no marks visible.
and the remains of the BTs mkd. by Tillman & Gawron in 1953-54
A decayed fir stump, 33" dia., bears S.38°W., 27.7 ft., no marks visible.
A fir stump, 53" dia., bears N.7°W., 56.8 ft., with no marks visible on partially open blaze.
and the bearing trees mkd. by Forkner in 2006-09
A fir, 13" dia., bears S.68°W., 34.2 ft., with a healed blaze and a Mag Nail at the base on right side center.
A fir, 12" dia., bears N.65°W., 21.9 ft., with a healed blaze and a Mag Nail at the base on right side center.
(Record and slope, 22.5 ft.)