

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T22-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1499)

Set post cor. of secs. 25, 30, 31 and 36.
Deposited charred stake, raised mound with trench and pts as per instructions.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13675)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S
R 8 W R 7 W
S 25 S 30
S 36 S 31
1964

from which

A W.Oak 18" dia., bears S.44°E., 590 lks. dist. mkd. T22S R7W S31 BT.

A W.Oak 18" dia., bears S.66½°W., 169 lks. dist. mkd. T22S R8W S36 BT.

A W.Oak 25" dia., bears N.68½°W., 76 lks. dist. mkd. T22S R8W S25 BT.

No suitable bearing trees available in section 30.