

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1505)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.25°E., 6 lks. dist.
A Fir 50" dia., bears S.63°W., 84 lks. dist.

F.J. Cole - Feb.1914 - Field Book 39 Page 11

Set Oak post for corner., from which
Fir 20" N.9½°E., 87 ft.
Fir 40" N.67°W., 79 ft.

A.R. Evans, D.C.S. - Wit: R.L. Matthews - Feb. 8, 1950 - C.S. File 44/18

Found - 40" Fir BT, N.67°W., 79.0 ft. Remarked BT.
Set 3/4" I.P. for corner.
New BT - Marked "¼ S", a 6" B.Oak, bears N.79°40'W., 58.7 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-121

Found - 3/4" Pipe set by Evans in 1950.
40" Fir stump, bark scribed, N.67°W., 79.0 ft.
8" B.Oak N.80°W., 58.7 ft. bark scribed "¼ S20 BT"
Corner pipe still in good condition. Did not set Brass cap.
New BTs -13" D.Fir N.47°E., 35.4 ft. mkd. ¼ S20 CS BT.
8" B.Oak N.80°W., 58.7 ft. mkd. ¼ S19 CS BT. (Evans tree)
Rotted Fir stump bears N.15°E., 4.0 ft. One orig. BT, a Fir was N.25°E., 4.0 ft.
Corner lies on very steep East slope approx. 125 ft. E. of top of ridge.

BLM resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #928, surveyed July/Aug. 1977 (DCSO records Vol. 40 Page(s) 16020)

The ¼ sec. cor., perpetuated and recorded by Evans in 1950, when original evidence was still in existence, and further perpetuated by Godfrey in 1962, monumented with an iron pipe 3/4" dia., firmly set, projecting 6" above ground, from which bearing trees mkd. by Godfrey
A Fir 18" dia., bears N.48½°E., 53 lks. dist. with healed blaze.
An Oak 9" dia., bears N.80°W., 91 lks. dist. with healed blaze.
(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
directly over iron pipe, with brass cap mkd:

T 22 S R 7 W

^{1/4}
S 19 | S 20
1977

Fd. Ok by K. DeGroot, 12/2006 - M146-51