

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1546-47)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S on W. face; from which
A Fir 20" dia., bears N.87°E., 40 lks. dist. mkd. ¼ S BT.
A Fir 14" dia., bears S.55½°W., 29 lks. dist. mkd. ¼ S BT
This cor. is on the NW. slope of ridge, 25 ft. above spur.

Wilford N. Haines, #239 - For: Woolley Logging Co. - Dec. 1963 - M 27-16

Set 1" x 1" x 36" T Iron, from which scribed:
48" I. Cedar S.47°W., 15.8 ft.
10" I. Cedar N.63°E., 10.0 ft.

David Edwards - For Seneca Jones Timber Co- 11/2004 - M145-72

Found - T-iron
21" Cedar N.63°E., 10.0' healed blaze.
New - 6" Fir S.85°W., 6.3'
6 ft. steel post 2 ft. south

Troy Rambo - For: Seneca Jones Timber Co. & Roseburg Resources Co. - 1/2011 - M161-71

Found - "T" iron & BTs per M27-16 & M145-72
Scribed- "¼ S4 BT" on a 14" DF - bears S.26°W., 18.2 ft.
"¼ S3 BT" on a 13" DF - bears S.60°E., 13.8 ft.