

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. H. Byars, under Contract #152 dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1528)

Set ¼ sec. post, from which
 A fir, 30" dia., bears N.80°E., 11 lks.
 A fir, 24" dia., bears S.10°W., 40 lks.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - 1962 - C.S. File 52/14-133

Corner searched for, not found.

Ken Hoffine - For: Juniper Timber Co. - June 2006 - M151-22

Set - 5/8"x40" iron rod with 2½" alum cap mkd LONE ROCK
TIMBER T22S R7W ¼ S22 & S27 2006 PLS 2291.
30" D.Fir bears S.82½°W., 57.7 ft. we scribe T22S R7W
¼ S27 BT & tag tree
14" D.Fir bears S.20½°E., 55.4 ft. we scribe T22S R7W
¼ S27 BT & tag tree
21" W.Fir bears N.58¼°E., 40.2 ft. we scribe T22S R7W
¼ S27 BT & tag tree
25" W.Fir bears N.8¼°W., 19.1 ft. we scribe T22S R7W
¼ S22 BT & tag tree

Corner sits in east-west fence line in small saddle approximately 175 ft south of old dirt road.

Note - We spent time searching for original evidence for the south ¼ of section 22, but we were unable to find any conclusive evidence of original corner location.

Fd. Ok by K. Hoffine 1/2008 - M158-38