

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Corner for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wilford N. Haines - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point"
18" Fir N.17°W., 16.2 ft.
30" Fir N.11°E., 23.0 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18068)

The ¼ sec. cor. of sec. 35 only, reestablished and recorded by Haines in 1957, monumented with a 1" T shaped iron rod, firmly set, projecting 10" above ground, with a washer 1" dia., mkd. Wilford N. Haines 239 Survey Point Drain Oregon from which the remains of bearing trees mkd. by Haines

A Fir 38" dia., bears N.13°E., 35 lks. dist. with scribe marks ¼ S35 BT visible on bark blaze.

A Fir snag 23" dia., bears N.18°W., 24 lks. dist., with scribe marks ¼ S35 BT visible on bark blaze.

At the corner point

Set an alum. post 28" long, 2½" dia., 24" in the ground, directly over iron rod, with alum. cap mkd: T 22 S R 7 W

1/4 S 35
T 23 S R 7 W
1984

from which a new bearing tree

A Grand Fir 27" dia., bears N.77°W., 58 lks. dist. mkd. ¼ S35 BT.