

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. 35 & 36 only, So. bdy.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1495)

Set standard cor. to secs. to 1 and 2, from which
A Laurel 6" dia., bears S.54°E., 35 lks. dist.
A Fir 40" dia., bears S.36°W., 71 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under special instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1469)

At the standard cor. of secs. 1 and 2, T23S R7W which I reestablish at the same point, as follows:
Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for standard cor. of secs. 35 and 36, T22S R7W, marked S C T22S R7W on N.; S36 on E.; and S35 on W. faces, with 1 groove on E. and 5 grooves on W. faces; from which
A Fir 6" dia., bears N.15°E., 25 lks. dist. mkd. T22S R7W S36 BT.
A Fir 8" dia., bears N.18°W., 19 lks. dist. mkd. T22S R7W S35 BT.
This cor. is on the Northerly slope of spur.

Wilford N. Haines - For: E.G. Whipple - Oct. 1957 - M 1-59

Set from original bearing trees.
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18066)

At the cor. of secs. 35 and 36, determined from the original bearing trees:
A Fir 15" dia., bears N.15°E., 25 lks. with healed blaze.
A Fir 24" dia., bears N.18°W., 19 lks. with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 7 W
S 35 S 36
S 1
T 23 S R 7 W
1984

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154

