

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1515)

-----  
Set post cor. to secs. 1, 2, 11 and 12, from which  
A Cedar 12" dia., bears N.60°E., 37 lks. dist.  
A Fir 16" dia., bears S.70°E., 38 lks. dist.  
A Fir 14" dia., bears S.25°W., 15 lks. dist.  
A Fir 14" dia., bears N.30°W., 40 lks. dist.

O.F. Thiel - For: Carl Binder - April 1943 - Fieed Book 117 Page 95

-----  
Two old bearing trees standing and a Cedar stake in place.  
(Set by a survey for Lee Barker)

Wilford N. Haines - For: Chester Sweringen and Harold Woolley 1956 - M 3-22

-----  
Found - Orig. Cedar N.60°E., 37 lks.  
Orig. W.Fir S.25°W., 15 lks.  
Found scribed stake.  
Set an angle iron with brass cap at point for corner scribed "Survey Point Wilford N. Haines #239".

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - May/June 1962 - C.S. File 52/14

-----  
Found - W.Fir now 48", S.25°W., 9.9 ft. Open scar and find portions of scribing on partly rotted old face.  
Cedar tree now 40", N.60°E., 24.4 ft. opened scar and find badly rotted old face, old axe marks found, but no scribing.  
Stump hole and rotted remains of W.Fir log, N.30°W., 26.4 ft. Too far gone for scars or scribing.  
Stump hole S.70°E., 25.1 ft.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 7 W

S 2 | S 1  
-----  
S11 | S12  
1962

New BTS -10" D.Fir S.41°E., 32.8 ft. mkd. T22S R7W S12 CSBT  
12" W.Fir N.59½°W., 42.6 ft. mkd. T22S R7W S2 CSBT  
10" D.Fir S.85°W., 27.4 ft. mkd. T22S R7W S11 CSBT  
8" W.Fir N.75°E., 34.3 ft. mkd. T22S R7W S1 CSBT.  
"T" Iron set by Haines bears N.78°W., 3.7 ft.

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cor. Fd. and used in BLM resurvey by Boyd W. Peterson, Cadastral Surveyor, under Group #1346, surveyed Sept/Dec. 1986 (DCSO records Vol. 48 Page 18308)

Ron Rice, NW Land Surveying - For: Seneca Jones Timber Co. - Oct. 2013 - C.S. File 65/79-18

-----  
Found - Brass cap with the following accessories:  
48" W.Fir rotted stump bears S.25°W., 9.9' no marks  
45" I.Cedar bears N.60°E., 24.4' healed face  
20" D.Fir bears S.41°E., 32.8' healed face  
31" W.Fir bears N.59½°W., 42.6' healed face  
Haines T Iron bears N.78°W., 3.7'  
Record 10" D.Fir S.85°W., 27.4' down  
Record 8" W.Fir N.75°E., 34.3' down  
Steel post adjacent to corner  
All accessories have red painted band and face plus bearing tree tag.

Fd as per rec. R. Rice 6/2016 - C.S. File 65/94-1