

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1514-15)

-----  
Set ¼ sec. post, from which  
A Fir 16" dia., bears N.28°E., 61 lks. dist.  
A Dogwood 8" dia., bears S.50°E., 47 lks. dist.

Wilford N. Haines - For: Chester Sweringen and Harold Woolley  
1956 - M 3-22

-----  
Corner located by proportional measurement.  
Set an angle iron with brass cap at corner point inscribed  
"Survey Point Wilford N. Haines #239", from which scribed:  
12" Fir S.62°W., 6.5 ft.  
8" Fir N.26°E., 7.0 ft.

Fd. OK, March 1994, Ken Hoffine, M 119-23  
FD. OK by D. Edwards, Oct. 1999 - CS 65/25-8

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch  
- Feb. 8, 2013 - C.S. File 67/38-8

-----  
Found - A 1" dia., brass washer (properly mkd) on a 1"x1"  
"T" iron firmly and plumbly set, protruding 10"  
above ground.  
No stumps or trees in area large enough or old  
enough to be OBTs  
A 12" now a 24" dia., 4½ ft. tall D.Fir stump with  
a fully healed single blaze; bears S.62°W., 6.5  
ft. (as per rec.) 1956  
An 8" fir now a 12" dia., 5½ ft. tall D.Fir stump  
with a fully healed single blaze; bears N.29°E.,  
7.0 ft. (rec. N.26°E., 7.0 ft) 1956  
New - Proportioned in 1956 monument is stable and in good  
condition; we leave as found.  
A 5" dia., G.Fir scribed "X" "CSBT" on a high-low;  
bears N.73°E., 10.1' ft.  
A 7" dia., D.Fir scribed "X" "CSBT" on a double  
blaze; bears South 6.1 ft.  
A 6" dia., D.Fir scribed "¼S12CS" "BT" on a double  
blaze; bears West, 24.4 ft.  
No suitable trees in NW quadrant.  
Note - Monument is on gentle north slope in young reprod  
fir forest. Monument is just north and west from  
NW corner of an older fire regrowth fir forest.