

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. cor. for 24 & 25 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1431)

-----  
Set post cor. of secs. 19, 24, 25 and 30, from which  
A Fir 10" dia., bears S.60°W., 45 lks. dist.  
A Fir 36" dia., bears S.18°E., 69 lks. dist.  
A Fir 12" dia., bears N.26°W., 38 lks. dist.  
A Hemlock 14" dia., bears N.45°E., 72 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1461 and 1542)

-----  
(On page 1461): "The old cor. of secs. 19, 30, 24 and 25, of which the only remaining indication is one bearing tree - bears S., about 150 lks. dist" (from sec. cor. established for 19 and 30 only, T22-6)

(On page 1542): At point of intersection, I  
Set a sandstone 12x8x8 ins. 8" in the ground, for closing cor. of secs. 24 and 25, mkd. C C on W., with 2 grooves on N. faces; from which

A Maple 5" dia., bears S.68°W., 46 lks. dist. mkd. T22S R7W S25 BT.  
A Cedar 14" dia., bears N.8°W., 57 lks. dist. mkd. T22S R7W S24 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & Clete Putnam, crew - Aug. 1961 - C.S. File 49/143-66

-----  
Found - Haines T Iron and cap. (No record source found)  
Maple tree, now 10", S.68°W., 31.0 ft., previously opened, old scribing visible in opened face.  
New BTs -28" R.Cedar N.8°E., 26.3 ft. mkd. "CC S24 S25 CS BT"  
12" Maple S.39°E., 13.5 ft. mkd. "CC S24 S25 CS BT"

Fd. OK, July 1990, C.S. File 63/104

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5

Fd. OK, Jun. 1995, K. Hoffine, C.S. File 65/1-5