

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1432)

Set post cor. of secs. 13, 18, 19 and 24, from which
A Fir 20" dia., bears S.78°W., 20 lks. dist.
A Fir 12" dia., bears S.35°E., 37 lks. dist.
A Fir 12" dia., bears N.77°E., 37 lks. dist.
A Fir 30" dia., bears N.50°W., 82 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1460)

The cor. of secs. 18, 19, 13 and 24, I find in a dilapidated condition. I reestablish same from the bearing trees as follows:

Set a Madrona post 3 ft. long, 4" sq., 24" in the ground, mkd. T22S S18 on NE.; R6W S19 on SE.; S24 on SW.; and R7W S13 on NW. faces; with 3 notches on N. and S. edges; from which
A Fir 16" dia., bears N.77°E., 37 lks. dist. mkd. T22S R6W S18 BT.
A Fir 12" dia., bears S.35°E., 31 lks. dist. mkd. T22S R6W S19 BT.
A Fir 20" dia., bears S.72°W., 20 lks. dist. mkd. T22S R7W S24 BT.
A Fir 36" dia., bears N.50°W., 81 lks. dist. mkd. T22S R7W S13 BT.

Wilford N. Haines - Haines field book H-117 (date ?)

An 8" Chinck N.14½°W., 28. ft.
5" Fir S.48°W., 32.5 ft.
34" Fir S.67°E. (Orig.) 24.42 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Aug. 23, 1961 - C.S. File 49/143-62

Corner Report Only

Found - Haines T Iron and cap at corner.
Fir tree, now 30" dia., N.77°E., 24.4 ft. Has been previously opened and scribing "6" can be seen in opened scar.
Fir stump now 38" dia., S.72°W., 13.2 ft., shows scar.
Stump hole N.50°W., 53.5 ft.
No trace of SE BT found.

(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. cor. for 13 & 24; 18 & 19, T22-6

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Found recently bark scribed Fir tree, 34" dia.,
S.68°E., 56.2 ft. mkd. T22S 6W 19.
7" D.Fir S.47°W., 32.4 ft. Scr grown over.
12" Chinquapin N.14°W., 28.1 ft. mkd. T22 R7 S13.

Ken Hoffine - for Lone Rock Timber Co. - Dec. 1994 - M 121-43

Corner Report Only

Found - Haines T-iron .3' above ground
36" D.Fir stump, bears S.72°W. 13.5', no marks
visible
27" D.Fir "high" stump, bears N.77°E. 25.2' chopped
out face. scribing barely visible.
70" D.Fir "high" stump, bears S.70°E. 55.7', bark
scribing visible.
20" D.Fir, bears S.46°W. 32.5', we scribed 22S 7W
S24 B.T. & tagged.

Corner lies on a 40% slope to the Northwest

Fd. Ok, Jun. 1995 - K. Hoffine - C.S. 65/1-5

Ken Hoffine - For: Lone Rock Timberland Co. - Nov. 2009 -
M160-18

Found - Haines T-Iron with washer on top.
38" D.Fir stump bears S.74¼°W., 13.4 ft. (Rec.
S.72°W., 13.5 ft.) chopped out face & tag.
27" high D.Fir stump bears N.77¼°E., 24.8 ft. (rec.
N.77°E., 25.2 ft.) chopped out face & tag.
40" high D.Fir stump bears S.66°E., 55.1 ft. (rec.
S.70°E., 55.7 ft.) bark scribed.
20" D.Fir bears S.47¼°W., 32.3 ft. (rec. S.46°W.,
32.5 ft.) healed face & tag.

Corner lies approx. 150 ft. west of end of existing dirt road
and on West facing slope.