

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2732)

-----  
Set post, 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 9, 10, 15, & 16, marked T23S S10 on NE, R10W S15 on SE, S16 SW, and S9 on NW face, with 4 notches on S and 3 notches on E edge; from which

- A Fir, 6" dia., bears N.20°E., 34 lks., mkd: T23S R10W S10 BT.
- A Fir, 8" dia., bears S.52°E., 32 lks., mkd: T23S R10W S15 BT.
- A Fir, 10" dia., bears S.39°W., 30 lks., mkd: T23S R10W S16 BT.
- A Fir, 6" dia., bears N.28°W., 23 lks., mkd: T23S R10W S9 BT.

Oregon St. Board of Forestry - Elbert Driver, Engineering Aide - Witnesses: Bob Banks, Derald Timmons & Dick Rugh - Sept. 13, 1957 - C.S. File 42/314

-----  
Found - Orig. post, down & rotted, scribed 9, 10, 15, & 23S & portion of T, 16 R10W visible, from which  
6" Fir bears N.20°E., 34 lks., now 18" dead tree, scribes S10 visible. Also (not orig.) scribed 2 10 R BT visible above orig. face.  
10" Fir bears S.39°W. 30 lks. now 35", face unexposed  
8" Fir bears S.52°E. 32 lks. now 24", face unexposed  
6" Fir bears N.28°W., 23 lks., now 27", exposed by unknown parties, scribes T23 visible.  
Set - 1½"x36" galv. IP with 3" br. cap mkd: Ore. St. Bd. of Forestry S9 S10 S15 S16 1957 RS359, 33" in ground, in mound of stone, and from which a:  
26" Fir bears N.69°E., 31.3 ft. scribed T23S R10W S10 BT.  
27" Fir bears N.6°E., 26.4 ft., scribed RS359.  
Oregon St. Board of Forestry metal location poster on 27" Fir N.6°E., 26.4 ft.

Please note that this corner is on the Douglas Co. & Coos Co. line and Coos Co. Surveyor's Office may have more information concerning this corner.