

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2723)

Set a Fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ secs. cor. mkd: ¼ S27 on N and 34 on S face; from which
 A Fir, 13" dia., bears S.53°E., 14 lks., mkd: ¼ S34 BT.
 A Fir, 13" dia., bears N.59°W., 19 lks., mkd: ¼ S27 BT.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 7 & C.S. File 49/80 (Filed 4/24/1958)

Old corner post & orig. BTs located:
 18" Fir N.59°W., 12.5 ft. OBT
 16" Fir S.53°E., 16 ft - OBT
Replace post with 3"x3' Hemlock

Arnold G. Gibson, Oregon St. Board of Forestry - 12/14/1961 - C.S. File 42/422

Found - Orig. fir post, now missing, from which a:
 13" Fir bears S.53°E., 14 lks., now 17", exposed scribes S34.
 13" Fir bears N.59°W., 19 lks., now 25", face grown over.
Set - 1½"x36" galv. IP with 3" bronze cap mkd: "Ore. St. Bd. of Forestry ¼ S27 S34 1961 RS359", 32" in ground, in mound of stone, & from which a:
 21" Fir bears N.16°W., 51.1 ft., scribed RS359.
 Ore. St. Bd. of Forestry metal location poster on orig. 13" Fir BT NW.
 4"x4"x72" white painted cedar post 1.5' NE of pipe.

James M. McIntosh - For: Oregon Dept. of Forestry - 7/1999 - M 133-14

Found - Oregon ST. Dept. of Forestry 1½"x36" Alum. pipe with 3 3/4" alum. cap w/magnetic insert 34" in ground.
 18" Fir N.1°E., 69.7 ft. to alum. nail in BT face scribed ¼ S27 BT. BT tag.
 WP N.52°E., 3.5 ft. to base.
 7" Hemlock S.2°E., 4.7 ft. to aluminum nail in BT face scribed ¼ S34 BT. BT tag.
 WP S.38°W., 1.8 ft. to base.
 1" iron pipe S.73°E., 0.45 ft.
Note - Information below is taken from Weyerhaeuser records dated 1978
continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

55" Fir stump N.24°W., 121.3 ft.
20" Fir stump N.77½°E., 65.1 ft.
10" Maple S.82½°W., 62.2 ft.
Bearing & distances were measured from the spikes in the 2 remaining Fir stumps to the 1" IP. Those measurements are shown below.
55"x2' high rotted stump N.19°W., 121.9 ft.
14"x1' high rotted stump N.77°E., 68.0 ft.