

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 500538

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 11 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2735)

Set a Fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. on W. bdy. of sec. 11, marked ¼ S on W and 11 on E face; from which

A Fir, 20" dia., bears S.47¼°W., 121 lks., mkd: ¼ S BT.

A Madrona, 6" dia., bears N.60°E., 114 lks., mkd: ¼ S11 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - For: "West Shore Lodges Subdivision, Mr. Rose & Mr. Lee - Feb/May 1958 - M 8-72 & C.S. File 49/90

Found - Orig. 20", now 56" Fir S.47¼°W., record 79.9 ft. I find should be 83.9 ft., open & find good scribing " } "

Note: This BT also used as BT for E ¼ cor. S10. Clump of Alders that checks bearing & dist. to record Madrone. A down Alder has small section of apparent old face, no scribing visible.

Note - Bearing & distance between ¼ corners check record.
Set - Brass cap at corner mkd: W ¼ T23S R10W County Surveyors Office, 1958

28" R.Fir s.29°E., 123.00 ft. scribed ¼ S11 CS BT.

35" R.Fir N.53°E., 62.4 ft. scribed ¼ S11 CS BT.