

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2739)

-----  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S3 on W., and 2 on E face, from which  
A Fir, 30" dia., bears N.36°E., 24 lks., mkd: ¼ S2 BT.  
A Fir, 30" dia., bears S.48°W., 25 lks., mkd: ¼ S3 BT.

Arnold G. Gibson, Oregon St. Board of Forestry - Elbert Driver, Transitman - Wit. D. Timmons, R. Witham, R. Huff - 2/7/1958 - C.S. File 42/331

-----  
Found - Orig. post, now missing, found rotted stake point, from which a:  
30" Fir bears N.36°E., 24 lks., now 38", scribe B exposed, remainder unexposed.  
30" Fir bears S.48°W., 25 lks., now 30"x2' rotted stub.  
Set - 1½"x36" gal. iron pipe with 3" bronze cap mkd: OREGON STATE BOARD OF FORESTRY ¼ S2 S3 1958 RS359, 33" in ground, & from which:  
40" Fir bears S.68 ¾°E., 30.2 ft., scribed RS359  
40" Fir bears S.51¼°W., 31.8 ft., scribed ¼ S3 BT.  
Oregon State Board of Forestry metal location poster on 40" Fir BT SW.