

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Gregory K. Miller L.S. #2004 - For: Champion International Corp. - June thru Oct. 1984 - M 97-68 & C.S. 58/146

Set - 2½" brass cap attached to 2½"x30" galv. IP with flared bottom and mkd: "T23S R10W C ¼ S26 1984 RPLS 2004"
16" Cedar bears S.62°E., 17.8 ft.
46" Fir bears N.82°W., 46.0 ft., scribed "C¼ S26 BT"

James McIntosh, Oregon Dept. of Forestry - Tim VanVleet & Ralph C. Hall - Jan. 21, 2003 - C.S. File 65/45-8

Found - 2½" galvanized iron pipe with 2½" brass cap (in place) from which a:
16" Cedar S.62°E., 17.8 ft.; now 17" x 4 ft. high stump in place, scribes visible, Champion Timberlands tag.
46" Fir N.82°W., 46.0 ft. now 47"x4 ft. high stump in place, scribes visible, Champion Timberlands tag.
Rewitnessed from the above pipe & cap -
Carsonite witness post N.28°W., 3.6 ft. to base.
Carsonite witness post N.81°E., 2.2 ft. to base.
Carsonite witness post S.14°E., 2.5 ft. to base.
Carsonite witness post S.75°W., 4.5 ft. to base.
Magnetic variation set at 20°East.