

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2714)

Set Yew post, 4 ft. long, 5 ins. dia., 20" in ground for the $\frac{1}{4}$ sec. cor. between secs. 11 & 14, from which
 A Fir, 24" dia., bears N.40°E., 47 lks.
 A Fir, 36" dia., bears S.50°W., 15 lks.

GLO resurvey and retracement by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page 2754)

Intersect the $\frac{1}{4}$ sec. cor., which is a yew post, firmly set, marked and witnessed as described by the Surveyor General. The BTs being dead & marks on post illegible, I remark the post, $\frac{1}{4}$ S11 on N., & 14 on S face, from which
 A Fir, 8" dia., bears N.30°W., 13 lks., mkd: $\frac{1}{4}$ S11 BT.
 A Fir, 8" dia., bears S.17°W., 14 lks., mkd: $\frac{1}{4}$ S14 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S.A. Bilow - For: Mr. Rose & Mr. Lee "West Shore Lodges" - Feb. - May 1958 - C.S. File 49/90

Found - Both BTs, scribed 1906 resurvey.
 I open NW BT & find good scribing "BT"
 SW BT shows good scar, I do not open. Both now 13".
 Find bottom section of orig. corner stake under surface.

Set - Brass cap @ cor mkd: $\frac{1}{4}$ S11 T23S R10W COUNTY SURVEYORS
 S14 OFFICE 1958
 14" R.Fir bears North 19.8 ft. scribed $\frac{1}{4}$ S11 CS BT.

Oregon Dept. of Forestry, James M. McIntosh - Jennifer M. Griffith - Sept. 19, 2002 - C.S. File 64/44-21

Original
 Yew Post (missing) from which a:
 24" Fir N.40°E., 47 lks; now 36"x4' high very rotted stump in place, no marks visible.
 36" Fir S.50°W., 15 lks., now rotted flush with ground.

Walker, 1905 - from the orig. yew post:
 8" Fir N.30°W., 13 lks; now 16"x2' high stump in place, face closed, added bearing tree tag.
 8" Fir S.17°W., 14 lks; now 20"x4' high stump in place, face closed, added bearing tree tag.

Douglas Co. Surveyor, 1958 - Iron pipe with brass cap from which a:
 14" Fir North 19.8 ft.; now 20"x2' high stump in place, face closed, added BT tag. continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Rewitnessed from the above pipe & cap:
Carsonite witness post N.42°E., 2.7 ft. to base.
Carsonite witness post S.59°W., 3.2 ft. to base.
Mag. variation set at 20°E.