

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO rec. Vol. 7 Page(s) 2704)

Set Fir post, 4 ft. long, 5 ins. dia., 18" in ground for the 1/4 sec. cor. between secs. 23 & 24, from which
A Hemlock, 30" dia., bears S.30°E., 20 lks.
A Cedar, 36" dia., bears S.25°W., 23 lks.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg42

Found 1/4 cor. to secs. 23, 24, T23S R10W set by County Surveyor (?)
A 4"x4"x4' Cedar post 2' in ground, from which
An 8" Hemlock bears S.17°E., dist.
A 15" Fir bears S.32°W., dist.
Note - No distances were given on this corner report & I do not find any record of the County Surveyor's Office being at this corner. 9/7/1999 Jean Crawford DCSO

Oregon St. Forestry Dept., Arnold G. Gibson - Witnesses: Kucera, Cook, Fitch, & Bushmeier - Aug. 29, 1967 - C.S. File 55/50

Set - Ore. St. Bd. of Forestry 1 1/2"x36" IP with 3" bronze cap, 34" in ground.
27" Fir S.30°E., 12.15 ft. (RS359) Yellow metal location poster.
32" Fir S.58°W., 30.5 ft.
Creek course East, N.0°07'19"W., 33.0 ft.
4"x4"x72" white painted cedar post S.25°E., 1.3 ft.
1/2" Iron pipe N.27°55'W., 87.5 ft.

Fd. Ok by Lloyd Smith, 9/29/1981 M89-40
Fd. Ok by Gregory K. Miller, April/Aug. 1983 M95-29A