

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2708)

Set a Fir post, 5 ft. long, 5 ins. dia., 20" in ground for the ¼ sec. cor. between secs. 1 & 12, from which
A Laurel, 6" dia., bears N.10°E., 25 lks.
A Laurel, 5" dia., bears S.60°W., 33 lks.

A.R. Evans - Wit: J.E. Clinton and P. Duckett - Feb. 1952 - C.S. File 41/6

Found Orig. BT, Laurel N.10°W., 25 lks.
Marked cross on rock in place for corner.
Blazed and scribed N.B.T.s
14" Fir S.25°W., 22.0 ft., mkd: ¼ S12 RE 2741 BT
24" Fir, N.60°E., 27.0 ft. mkd: ¼ S1 RE 2741 BT

Wm. C. Stiles - For: SEEK, Inc. - Sept. 13, 1968 - C.S. File 55/89 and M 36-42

Set 2½" brass cap mkd. SEEK, Inc.
 T 23 S R 10 W
 ¼ S 1
 S 12
 1968
New BOs: 12" Maple S.72°E., 13.0 ft. mkd: ¼ S12
 6" Cross in rock wall N.76°W., 20.5 ft. mkd: ¼ S1.

Robert Ward - For: Lloyd Keeland - 4/2007 - M 152-70

Found - 2½" Brass cap dated 1968
 18" Maple bears S.75°E., 21.0' - healed face.