

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T23-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 6 Page(s) 2630)

-----  
Set Chitem-wood post 36 x 5, 18" in ground for corner to secs. 13, 18, 19 and 24, from which  
A Fir 60" dia., bears N.25°E., 62 lks. dist.  
A Maple 6" dia., bears S.25°E., 18 lks. dist.  
A Maple 14" dia., bears S.75°W., 14 lks. dist.  
A Maple 12" dia., bears N.22°W., 57 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #658 - Surveyed Oct/Nov. 1967 - (DCSO records Vol. 36 Page(s) 14602-03)

-----  
The Sec. Cor., determined at intersection of fences extending N., E., and W. This point has been used by local landowners for many years as the corner and is accepted as the best available evidence of the position of the original corner.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:  
T 23 S  
R 10 W R 9 W  
S 13 S 18  
S 24 S 19  
1967

from which  
A Myrtle 8" dia., bears N.69°E., 339 lks. dist. mkd. T23S R9W S18 BT.  
A Maple 8" dia., bears N.25°W., 648 lks. dist. mkd. T23S R10W S13 BT.  
No other suitable trees available within limits.

Robert W. Ward - For: Champion International Corp. - Nov. 1981 - M 89-63

-----  
Found - 2½" BLM brass cap on a 2½" I.P. set in 1967.  
8" Myrtle bears N.69°E., 223.7 ft. scribed T23S R9W S18 BT. (1967)  
8" dead, down Ash (rec. Maple) bears N.27°W., 427.7 ft. scribing not found. (1967)  
New BT - 11" Ash bears N.02°E., 81.3 ft. scribed T23S R9W S18 BT.

Fd. OK, Nov. 1995 by T. Hoshell - M 123-13

continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by John A. Farmer, Cadastral Surveyor, under Group #1789, surveyed Sept. 1995/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19848-9)

-----  
The cor. of secs. 13, 18, 19 & 24, monumented with an iron post, 2½" diam., firmly set flush with the ground, with brass cap mkd.  
T23S

R10W	R9W
<u>S 13</u>	<u>S 18</u>
S 24	S 19
1967	

from which the remains of bearing trees mkd. by Beck  
A myrtle, 7" diam., bears N.68½° E., 339 lks., no marks visible on open decayed blaze. (Record N.69°E.)  
a bearing tree not of known record

An ash, 15" diam., bears N.0½°E., 122 lks., with illegible scribe marks on partially healed blaze.  
and a new bearing tree

A twin ash, 6" diam., bears N.89¼°W., 341 lks., mkd. T23S  
R10W S13 BT.

No other suitable accessories available.  
The corner is located at the intersection of fences which extend N, E, and W.