

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 48" dia., bears N.15°E., 27.7 ft., no marks visible.

A fir stump, 36" dia., bears S.33°W., 37.0 ft., no marks visible.

and the bearing trees mkd. by Beck in 1967

A hemlock, 23" dia., bears N.15°E., 35.0 ft., with a healed blaze.

A hemlock, 23" dia., bears S.9°E., 18.5 ft., with a healed blaze.

A hemlock, 14" dia., bears S.42°W., 27.4 ft., with a healed blaze.

A hemlock, 17" dia., bears N.11°W., 29.7 ft., with a healed blaze.

From the corner

N.1°33'40"W., 135 ft dirt road, 10 ft wide, bears East & West

Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.

NAD 1983 (2011)

Latitude: 43°34'23.30"N. Longitude: 123°49'03.01"W.