

PRIMARY CORNER DESCRIPTION C.C. for Secs. 6 & 7 only, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #688 dated June 9, 1898 (DCSO records Vol. 7 Page(s) 2696-97)

At point of intersection, (N.1°W. 38.58 chs. dist. of old cor. of 1, 6, 7 and 12) I set an Alder post, 3 ft. long, 4' sq., 24" in the ground for closing cor. of secs. 6 and 7, mkd. CC T23S R9W on E.; S6 on N.; S7 on S. faces, with 1 groove on N. and 5 grooves on S. faces, from which
A Fir 6" dia., bears N.38½°E., 16 lks. dist. mkd. T23S R9W S6 BT.
A Fir 30" dia., bears S.24°E., 133 lks. dist. mkd. T23S R9W S7 BT.

Arthur R. Evans - Wit: J.I. Clinton and Elvin DeGrath - Feb. 25, 1952 - C.S. File 41/6

Found - Fir BT, N.38½°E., 16 lks.
Set 4" x 4" x 36" Fir stake.
Blazed and scribed new BT:
8" Fir S.42°E., 28.1 ft. mkd. CC S7 T23S R9W RE 2741 BT.

Arnold G. Gibson - For: Oregon State Board of Forestry - Oct/Nov. 1967 - C.S. File 55/68-1

Found - Original post, now missing.
6" Fir bears N.38½°E., 16 lks., now 17", exposed scribe C.
30" Fir bears S.24°E., 133 lks.; now destroyed by road.
Ridge, course S.50°W., bears South 2.08 chs.; in place.
1952 Evans 4"x4"x36" Fir stake, found in place from which a
8" Fir bears S.42°E., 28.1 ft., now 9" Fir, in place, face pitched over.
Set 1½" x 36" galv. iron pipe with 3" brass cap mkd. "Ore. St. Bd. of Forestry T23S S1 S6 S7 CC R10W R9W 1967 RS 359", 34" in ground, in place of Evans post, in mound of rock, and from which a:
24" Fir bears N.71°E., 20.0 ft. to face; scribed "T23S R9W S6 CC BT RS 359"
Set 4"x4"x72" white painted Cedar post, 1 ft. West of corner pipe.
OSBF metal location poster on 24" Fir, N.39°W., 9.5 ft.

(Cont. Next Page)

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 700639

PRIMARY CORNER DESCRIPTION C.C. for Secs. 6 & 7 only, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

True closing corner to sections 6 & 7: Set S.88°37'06"W.,
40.24 ft. of above C.C.
Set OSBF 1½" x 36" galv. I.P. with 3" bronze cap, from which
20" Fir N.31¼°E., 17.7 ft. (RS359) and yellow metal
location poster.
20" Fir S.82°E., 23.3 ft.
White painted Cedar post bears S.10°E., 1.0 ft.

BLM resurvey by James E. Jelley and Rolla R. Steward,
Cadastral Surveyors under Group # 703, surveyed July 1969/May
1970 (DCSO records Vol. 35 Page(s) 14550)

(Corner report only)

True point for the closing corner of secs. 6 and 7, T23S
R9W., determined and recorded by the OSBF in 1968, monumented
with an iron post, 1½" dia., firmly set, level with the
surface of the ground, with brass cap mkd. in 1968, from
which a bearing tree mkd. by the OSBF in 1968

A sawed Fir stump 20" dia., bears N.32°E., 28 lks. dist.,
with fragmentary scribe marks visible on open blaze.