

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 700669

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Arnold Gibson - For: Oregon State Board of Forestry
Marcy 15, 1968 - M 36-32

Set Ore. St. Bd. of Forestry 1½" x 36" galv. I.P. with bronze cap., from which
24" Fir N.62 3/4°W., 38.5 ft. (¼ S6 BT)
21" Fir S.80°E., 28.4 ft.
25" Fir S.27½°E., 31.4 ft. (RS 359) with yellow metal location poster.
Ridge top, course NE., South 65.0 ft.
White painted Cedar post bears N.E. 1.0 ft.

Arnold G. Gibson, Oregon St. Board of Forestry - Ed Kucera,
D. Smith, G. Gresham, W. Cook, & R. Ball - 7/1968 - M 36-32

Set - Oregon St. Bd. of Forestry 1½"x36" galv. IP eoyj 3
bronze cap, 34" in the ground.
24" Fir N.62 3/4°W., 38.5 ft. (¼ S6 BT)
21" Fir S.80°E., 28.4 ft.
25" Fir S.27½°E., 31.4 ft. (RS359) Yellow metal location poster
Ridge top, course NE, south 65.0 ft.
White post Cedar post 4"x4"x72" NE 1.0 ft.

BLM resurvey by James E. Jelley and Rolla R. Steward,
Cadastral Surveyors under Group # 703, surveyed July 1969/May
1970 (DCSO records Vol. 35 Page(s) 14551)

(1968 OSBF cap and 3 BTs found OK)
The corner point is located on top of spur ridge, bears NW.
and SE.