

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION C C Sec. 1, T23-10; & S. 6, T23-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 292 survey dated Aug. 7, 1878 (DCSO records Vol. 6 Page(s) 2632)

-----  
(N. on E. bdy. of Sec. 1 - T23S R10W)  
Intersect line, 26.00 chs. E. of Tp. corner.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #688, dated June 9, 1895 (DCSO records Vol. 7 Page(s) 2697)

-----  
Intersect N. bdy. of Tp. 210 lks. E. of cor. of secs. 6 and 1, which is a Fir post, 4" sq., 30" high, badly decayed, marked and witnessed as described by the surveyor general.

Oregon State Board of Forestry - March 15, 1968 - M 36-32

-----  
Set Ore. St. Bd. of Forestry 1½" x 36" galv. I.P. with bronze cap.  
BTs - 26" Fir N.72¼°E., 27.5 ft.  
      42" Fir S.38¼°W., 12.8 ft. (RS359) Yellow metal location poster.  
      46" Fir S.60°E., 34.8 ft.  
White painted cedar post bears N.W., 1.0 ft.

BLM survey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors, under Group #703, surveyed July 1969/May 1970 - (DCSO records Vol. 35 Page(s) 14549)

-----  
(Corner Report)  
The closing corner of Tps. 23 S., Rs. 9 and 10 W., determined and recorded by the OSBOF in 1968, monumented with an iron post, 1½" dia., firmly set, level with the surface of the ground, with brass cap mkd:

T 22 S R 9 W
S 31
S 1 S 6
R 10 W R 9 W
T 23 S
CC

from which bearing trees mkd. by OSBF in 1968:  
A Fir 28" dia., bears N.75°E., 44 lks. dist. with fragmentary scribe marks visible on open blaze.  
A Fir 45" dia., bears S.31½°W., 22 lks. dist. with fragmentary scribe marks visible on open blaze.