

PRIMARY CORNER DESCRIPTION NE Tsp Cor T25-1E

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Alonso Gesner, Deputy Surveyor, under Contract #659, dated May 21, 1896 - (DCSO rec. Vol. 21 Page(s) 9105)

Set basalt stone 14x10x8", 9" in the ground on hillside sloping SE, mkd with 6 notches on N, E, S, & W sides for cor. to Tps 24 & 25 S, Rs. 1 & 2 E, from which
A fir, 20" dia., bears N.47°E., 29 lks., mkd: T24S R2E S31 BT.
A pine, 20" dia., bears S.59°15'E., 75 lks., mkd: T25S R2E S6 BT.
A fir, 20" dia., bears S.15°W., 18 lks., mkd: T25S R1E S1 BT.
A fir, 8" dia., bears N.75°45'W., 21 lks., mkd: T24S R1E S36 BT.

GLO survey by John G Collins, US Engineer, under Special Instructions, dated March 12 1921 - Surveyed May 1926 - Aug. 1927 - (DCSO records Vol.21 Page(s) 9124A) and

GLO survey by Joseph A Ganong & John G Collins, US Cadastral Engineers under instructions dated March 12, 1921, surveyed May 1927/June 1928 - (DCSO Records Vol. 21 Page(s) 9124)

Pg 9124A
The old cor. of Tps. 24 & 25 S., Rs. 1 & 2 E. is a basalt stone, 6x10x8" above ground, firmly set, marked with 6 grooves on N, E, S, & W faces; from which
A fir, 24" dia., bears N.49°E., 29 lks., mkd: T24S R2E S31 BT. (Old BT)
A pine, 24" dia., bears S.63°E., 23 lks., mkd: T25S R2E S6 BT. (Old BT)
A fir, 24" dia., bears S.15°W., 18 lks., old BT with marks grown over.
A fir, 14" dia., bears N.69°W., not N.75°45'W., 21 lks., mkd: T24S R1E S36 BT. (Old BT)
Pg 9124 & 9124A
The cor. of Tps. 24 & 25 S., R1E, only, is a basalt stone, 6x10x8" above ground, firmly set, marked
24 S on N
25 S on S and
1 E on W face; from which
A fir, 24" dia., bears S.15°W., 18 lks., old BT with marks grown over.
A fir, 14" dia., bears N.69°W., 21 lks., mkd: T24S R1E S36 BT.