

PRIMARY CORNER DESCRIPTION NW township corner

Alias	Description

GLO survey by John G Collins, US Engineer, under Special Instructions, dated March 12 1921 - Surveyed May/Sept 1926 - (DCSO records Vol.21 Page(s) 9124A-9124B)

-----  
Set a basalt stone, 20x15x10", 15" in the ground, for closing cor. of Tps. 24 & 25 S., R2E, marked  
24 S on N  
CC and 2E and 6 grooves on E and  
25 S on S face;  
from which  
A fir, 24" dia., bears N.73°E., 82 lks., mkd: T24S R2E S31  
C C BT.  
A fir, 14" dia., bears S.53°E., 169 lks., mkd: T25S R2E S6  
C C BT.  
No iron post available for this corner.

Lane Co. Surveyors Office Department of Public Works - John Matthews - Bruce Bothel, PLS Associate Surveyor & Chris Larson, Engineering Tech 1 - Aug. 23, 2005 (file May 1, 2012, DCSO) - C.S. File 65/76-45

-----  
Found - At the corner position found a firmly set 6"x7" pyramidal shaped stone projecting 12" above grade on a steep hill side, 50' down hill from a gravel road, and marked per the 1927 GLO survey. The highpoint located on the northeast edge of the stone was used as the corner point. Found the stone with marks "24S" on the north face, "25S" on the south face, and "CC 2E" and six grooves on the east face.  
1927 - A 34" fir with healed face bears N.73°22'20"E @ 54.47' to face, 55.4' to center, and 36.9' to a silver magnet. (N.73°E. @ 82 lks = 54.1')  
New - Nothing needed. Accepted the stone as marking the corner position.  
2005 An 8" maple, blazed and scribed "CSBT" bears S.20°33'E., @ 22.97' to face, 23.3' to center, and 17.3' to a pink magnet.  
2005 Set a 2" alum. Cap "LCSO-RPI 2005" atop a 5/8" x 30" rebar bears N.88°34'10"W., 104.60'  
2005 Set a 2" alum. Cap "LCSO-RP2 2005" atop a 5/8" x 30" rebar bears N.20°09'30"W 49.11'  
Note - How to reach: from the intersection of ST. HWY. 138 & Forest Service RD #38 (39 miles East of Roseburg), Go 10 miles up RD 38 (Steamboat Creek) to RD 3815 on left. Go up it 5.5 miles to road 025 on right. Go up it 0.5 miles to a location tag on a large fir on the right. From tag walk N.60°E. 90' to the corner. continued next page

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW township corner

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Geographic map location - Use for navigation to corner area  
- not of survey grade accuracy.

Latitude = N.43°26'24".6      LONGITUDE = W.122°37'21".7  
NAD 83/91 values.

Basis of bearing - Bearings are true per GPS observations.

Equipment used - WILD TC-1010 TOTAL STATION & HP-48 GX DATA  
COLLECTOR.

BTs -      Distance to face refers to a P-K nail & brass washer  
            driven into the bottom of the face of new BTs, or  
            in a notch just below the healed blaze in fd BTs.

See CS file for sketch