

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION ¼ Cor Secs 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9328)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ cor. of secs. 29 & 30, with brass cap mkd

¼
S 30 | S 29
1928

from which

A fir, 14" dia., bears N.82°E., 12 lks., mkd: ¼ S29 BT.

A fir, 10" dia., bears N.32°W., 16 lks., mkd: ¼ S30 BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flauser;
Nov. 6, 1996 - C.S. File 65/9-32

Found - 2½" dia. properly marked brass cap on a 1" O.D. iron pipe, protrudes 11" above ground. (U.S. General Land Office Survey, 1928; Original corner)

14" now 26" dia. D.Fir with a fully healed single blaze, bears N.82°E., 6.0 ft. (rec. N.82°E., 7.9 ft. Distance fits well with a slope measurement). OBT

10" now 11" dia. D.Fir with a fully healed single blaze, bears N.28°W. 10.6 ft (rec. N.32°W. 10.6 ft. Bearing possibly read on wrong side of compass) OBT

New - 12" dia. D.Fir double blazed and scribed "¼ S29 CS BT" bears S.35°E., 9.5 ft.

9" dia. Maple double blazed and scribed "¼ S30 CS BT" bears S.30°W., 36.4 ft.