

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9311)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 28, 29, 32, & 33, with brass cap mkd

T25S	R2E
S29	S28
S32	S33

1928

from which

A fir, 10" dia., bears N.58°E., 57 lks., mkd: T25S R2E S28 BT.

A pine, 12" dia., bears S.36°E., 102 lks., mkd: T25S R2E S33 BT.

A fir, 28" dia., bears S.27°W., 61 lks., mkd: T25S R2E S32 BT.

A fir, 8" dia., bears N.29°W., 57 lks., mkd: T25S R2E S29 BT.