

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9300)

Set an iron post, 3 ft. long, 2" dia., 16" in the ground, to bed rock, and in mound of stone, 2 ft. base for cor. of secs. 21, 22, 27, & 28, with brass cap mkd

T25S R2E
S 21 | S 22
S 28 | S 27
1928

from which

- A hemlock, 8" dia., bears N.62°E., 22 lks., mkd: T25S R2E S22 BT.
- A fir, 18" dia., bears S.30°E., 55 lks., mkd: T25S R2E S27 BT.
- A fir, 16" dia., bears S.22°W., 17 lks., mkd: T25S R2E S28 BT.
- A hemlock, 12" dia., bears N.27°W., 115 lks., mkd: T25S R2E S21 BT.