

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9302)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 cor. of secs. 21 & 22, with brass cap mkd

1/4
S21|S22
1928

from which

A fir, 10" dia., bears S.62°E., 59 lks., mkd: 1/4 S22 BT.

A fir, 8" dia., bears S.30°W., 12 lks., mkd: 1/4 S21 BT.

Maurice E. Farr, U.S. Forest Service - Leonard Herzstein - May 8, 1984 - C.S. 62/15

Found - Orig. 1" I. Post bent flush with the ground w/properly mkd Brass Cap. Dug up I P - Orig 1928 - now 30" long w/top 12" bent over 60° w/bottom 18" still vertical in ground. I use the vertical position of the base as the orig. position of the corner, from which the remains of the orig. BTs

BTs - 18" D.Fir stump w/log alongside bears S.62°E., 38.5 ft. (Rec. 38.9 ft.), with healed blaze.

Set - 12" D.Fir snag bears S.30°W., 7.9 ft. w/healed blaze
I reset orig. mon. over orig. vert. position. Since I could not straighten the I.P., I buried the base, bent to north. & the top is set vert. & flush in a 3 ft. d. mound of stone.

6 ft. steel fence post about 2 1/2 ft. north of corner with USFS sign #54-4 attached.

New BTs- 20" I.Cedar bears S.39 3/4°E., 75.2 ft., scribed: 1/4 S22 BT, on a single blaze.

4" W.Fir bears N.54 3/4°W., 48.9 ft., scribed: 1/4 S21 BT, on a single blaze.

Note - Corner is 40 ft. north of new road (USFS Rd.#3816-150), 0.3 miles from jct. with USFS Rd.#3816-100.