

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9304-5)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

| | |
|------------|------------|
| T25S | R2E |
| <u>S 9</u> | <u>S10</u> |
| S16 | S15 |
| 1928 | |

from which

- A hemlock, 10" dia., bears N.82°E., 32 lks., mkd: T285S R2E S10 BT.
- A hemlock, 8" dia., bears S.42°E., 33 lks., mkd: T25S R2E S15 BT.
- A hemlock, 8" dia., bears S.10°W., 83 lks., mkd: T25S R2E S16 BT.
- A fir, 8" dia., bears N.55°W., 6 lks., mkd: T25S R2E S9 BT.