

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9287)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 22, 23, 26, & 27, with brass cap mkd

T25S R2E
S22 S23
S27 S26
1928

from which

- A hemlock, 8" dia., bears N.45°E., 37 lks., mkd: T25S R2E S23 BT.
- A chinquapin, 6" dia., bears S.62°E., 30 lks., mkd: T25S R2E S26 BT.
- A dogwood, 5" dia., bears S.63°W., 8 lks., mkd: T25S R2E S27 BT.
- A chinquapin, 9" dia., bears N.15°W., 46 lks., mkd: T25S R2E S22 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - Sept. 9, 1981 - C.S. File 61/27

-
- Found - 1928 orig. Brass Cap, firmly set, protruding 16" out of the ground & leaning slightly to the NW, properly marked.
 - BTs - NOTE: All measurements taken at the point the pipe enters the ground.
 - 14" hemlock (orig. 8") with well healed blaze bears N.37°E., (Rec. N.45°E.) 24.4 ft.
 - 9" Chinquapin with Forest Service BT Tag, bears N.24°W., 35.6 ft. (Rec. N.15°W., 30.4 ft.). I chop open and find no trace of scribing.
 - No trace of other Orig. BT's.
 - New BTs- 14" Fir, scribed "T25S R2E S27 CS BT" in double blaze, bears S.70°W., 51.4 ft.
 - 9" Hemlock scribed "T25S R2E S22 CS BT" in double blaze, bears N.83°W., 38.7 ft.
 - 34" Fir, bark scribed "T25S R2E S26 CS BT", bears S1°E., 54.8 ft.
 - Note - Corner lies West of F S Rd. No. 2529 (old)...(new) dead end off of 3816 approx. 350 ft.