

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9275-6)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd

T25S | R2E  
S14 | S13  
S23 | S24  
1928

from which

- A fir, 20" dia., bears N.78°E., 39 lks., mkd: T25S R2E S13  
BT.
- A fir, 10" dia., bears S.24°E., 37 lks., mkd: T25S R2E S24  
BT.
- A fir, 12" dia., bears S.86°E., 12 lks., mkd: T25S R2E S23  
BT.
- A fir, 8" dia., bears N.2°W., 64 lks., mkd: T25S R2E S14  
BT.